



Dimension Charts for Sectional Track

Sectional Doors Track Headroom and Backroom Clearance

Standard Lift Track

Headroom Clearance Dimensions

	Door Height	Centerline of Shaft	Minimum Headroom
2" Track	Thru 12'0"	O.H. + 11 5/8"	14 1/4"
15" Radius	Thru 16'0"	O.H. + 12 5/8"	15 3/4"
3" Track	Thru 18'0"	O.H. + 14 5/8"	18"
15" Radius	Thru 32'0"	O.H. + 16 7/8"	21 1/2"

O.H. = Opening Height

Standard Lift Track - Follow the roof

Headroom Clearance Dimensions

	Door Height	Centerline of Shaft	Minimum Headroom
2" Track	Thru 12'0"	O.H. + 11 5/8"	14 1/4"
	Thru 16'0"	O.H. + 12 5/8"	15 3/4"
3" Track	Thru 18'0"	O.H. + 14 5/8"	18"
	Thru 32'0"	O.H. + 16 7/8"	21 1/2"

O.H. = Opening Height

Low Headroom Track - Springs to front

Headroom Clearance Dimensions

	Door Height	Centerline of Shaft	Minimum Headroom
2" Track	Thru 12'0"	D.H. + 8"	11 3/4"
15" Radius	Thru 16'0"	D.H. + 8"	12 1/2"
3" Track	Thru 12'0"	D.H. + 9"	13"
15" Radius	Thru 18'0"	D.H. + 9"	13 3/4"

D.H. = Door Height

Low Headroom Track - Springs to rear

Headroom Clearance Dimensions

	Door Height	Centerline of Shaft	Minimum Headroom
2" Track	Thru 12'0"	D.H. + 2"	7 1/2"
15" Radius	Thru 16'0"	D.H. + 2"	8"
3" Track	Thru 18'0"	D.H. + 6 3/4"	9 3/4" *

D.H. = Door Height

Additional headroom required for drawbar operation

** Chain hoist with cross header shaft requires 3 1/2" additional headroom*

Dimension Charts: Sectional Track

Lift Clearance Track* - Standard Headroom Clearance Dimensions

	Door Height	Centerline of Shaft	Minimum Headroom
2" Track 15" Radius	Thru 16'0"	O.H. + L.C. + 5 5/8"	L.C. + 12"
3" Track 15" Radius	Thru 32'0"	O.H. + L.C. + 6 5/8"	L.C. + 13"

O.H. = Opening Height; L.C. = Lift Clearance

* For applications where additional headroom clearance is required.

Lift Clearance Track* - Follow the roof Headroom Clearance Dimensions

	Door Height	Centerline of Shaft	Minimum Headroom
2" Track 15" Radius	Thru 16'0"	O.H. + L.C. + 5 5/8"	L.C. + 12"
3" Track 15" Radius	Thru 32'0"	O.H. + L.C. + 6 5/8"	L.C. + 13"

O.H. = Opening Height; L.C. = Lift Clearance

* For applications where additional headroom clearance is required.

Full Vertical Track Headroom Clearance Dimensions

	Door Height	Centerline of Shaft	Minimum Headroom
2" Track	Thru 16'0"	O.H. + O.H. + 3/8"	O.H. + 11"
3" Track	Thru 28'0"	O.H. + O.H. + 3/8"	O.H. + 11"

O.H. = Opening Height