

COLD STORAGE ACCESS SOLUTIONS

RAPIDFLEX AND RAPID FREEZE HIGH SPEED DOORS

Cold storage facilities require solutions that are highly rated in areas such as thermal performance, air infiltration standards and cleanliness. We have developed specific product solutions to fit these critical needs for the cold storage industry.

RAPIDFLEX® MODEL 991

- Air tight design reduces air exchange to no higher than .236 cfm/sf (ASTME-283)
- Air infiltration rating to tightly control the interior airflow
- FDA/USDA - Compliant fabric and stainless steel guides and hood to help facilitate cleanliness
- Specialized for processing areas
- Max width of 14'
- Max height of 14'
- Max opening speed of 70" per second
- Max closing speed of 40" per second
- 5-Year Limited Warranty
- Application-dependent ambient or heated air curtain available



RAPIDFREEZE® MODEL 997

- Insulated curtain provides a barrier to prevent heat loss and condensation
- Actively heated guides ensure the complete height of the guide has a uniform temperature to ensure smooth door movement
- Patented quad-sealed, insulated guides prevent guide and conditioned air loss around the curtain
- Max width of 12'
- Max height of 18'
- Max opening speed of 80" per second
- Max closing speed of 40" per second
- 5-Year Limited Warranty
- Application-dependent ambient or heated air curtain available



2501 S. State Hwy. 121 Bus., Suite 200, Lewisville, TX 75067
1-800-929-DOOR • sales@overhaddoor.com
overhaddoor.com

©2024 Overhead Door Corporation. Overhead Door and EverGuard are trademarks and RapidSlat, Stormtite, Powderguard and the Red Ribbon logo are registered trademarks of Overhead Door Corporation. All other trademarks are property of their rightful owners. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation. C900-1454 07/24



INDUSTRY LEADING
COMMERCIAL & INDUSTRIAL SOLUTIONS