

The Genuine. The Original.



**SECTION 083323
UPWARD COILING DOORS
MODEL 610**

PART 1 GENERAL

1.01 SECTION INCLUDES

- A. Upward coiling service doors.

1.02 RELATED REQUIREMENTS

- A. Section << **079200 - Joint Sealants**>>: Sealing joints between frames and adjacent construction.
- B. Section << **087100 - Door Hardware**>>: Cylinder cores and keys.
- C. Section << **260583 - Wiring Connections**>>: Power to disconnect.

1.03 REFERENCE STANDARDS

- A. ASHRAE Std 90.1 I-P - Energy Standard for Buildings Except Low-Rise Residential Buildings; Most Recent Edition Adopted by Authority Having Jurisdiction, Including All Applicable Amendments and Supplements.
- B. ASTM A653/A653M - Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process; 2023.
- C. ASTM E330/E330M - Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference; 2014 (Reapproved 2021).
- D. FBC TAS 201 - Impact Test Procedures; Testing Application Standard; 1994.
- E. FBC TAS 202 - Criteria for Testing Impact and Non-Impact Resistant Building Envelope Components Using Uniform Static Air Pressure; Testing Application Standard; 1994.
- F. UL (DIR) - Online Certifications Directory; Current Edition.

1.04 SUBMITTALS

- A. Product Data: Submit manufacturer's standard literature showing materials and details of construction and finish.<< **Include data on electrical operation.**; or **None - N/A**>>
- B. Shop Drawings: Indicate rough and actual opening dimensions, anchorage methods, hardware locations, and installation details.
- C. Manufacturer's Instructions: Indicate installation sequence and installation, adjustment, and alignment procedures.
- D. Installer's qualification statement.

- E. Operation and Maintenance Data: Indicate modes of operation, lubrication requirements and frequency, and periodic adjustments required.
- F. Specimen warranty.

1.05 QUALITY ASSURANCE

- A. Manufacturer Qualifications: Company specializing in performing work of this section with minimum of << **5 years**; or _____ years>> of << **documented**; _____; or **None - N/A**>> experience in fabrication and installation of security closures.
- B. Installer Qualifications: Company specializing in performing work of this section with minimum of << **3 years**; or _____ years>> of << **documented**; _____; or **None - N/A**>> experience and approved by manufacturer.
- C. Products Requiring Electrical Connection: Listed and classified by << **UL (DIR); TUV; testing firm acceptable to authorities having jurisdiction**; or _____>> as suitable for purpose specified.

1.06 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Protect materials from exposure to moisture.
- C. Store materials in dry, warm, ventilated, weathertight location.

1.07 WARRANTY

- A. Manufacturer Door-Only Warranty: Provide manufacturer warranty for door assembly for duration indicated under individual doors. Complete forms in <<Owner>>'s name and register with manufacturer.
- B. Manufacturer Door and Operator Warranty: Provide manufacturer's limited warranty for door and operator system free from material and workmanship defects for duration and cycles indicated under individual doors; counterbalance spring and finish not covered by warranty.

PART 2 PRODUCTS

2.01 MANUFACTURER

- A. Overhead Door Corporation; www.overheaddoor.com; 1 (800) 929-3667.
- B. Substitutions: Not permitted.

2.02 UPWARD COILING SERVICE DOORS

- A. Overhead Door™ Brand; Model 610.
 1. Slats: Interlocking, roll-formed, metal slats.
 2. Width: _____ **feet (_____ mm)**.
 3. Height: _____ **feet (_____ mm)**.
 4. Mounting: << **Surface-mounted on side indicated on drawings**; or **Between jamb**>>.
 5. Opening Speed: Door to operate at variable speed of << **6 to 12 inches (152 to 305 mm)**>> per second.
 6. Closing Speed: Door to operate at variable speed << **6 to 12 inches (152 to 305 mm)**>> per second.
 7. Operation Cycles: Capable of operating for minimum 20,000 cycles. One operation cycle is complete when door is opened from closed position to fully open position and returned to closed position.
 8. Available Warranty:

- a. Door Only: Two years.
 - b. Door and Operator Warranty: Three years or 20,000 cycles, whichever comes first.
9. Wind Load: Design door assembly to withstand ultimate static pressure load of << **20 psf (0.96 kPa); 26 psf (1.25 kPa); 31 psf (1.48 kPa); 36 psf (1.72 kPa); 41 psf (1.96 kPa); 50 psf (2.39 kPa); 57 to 130 psf (2.73 to 6.22 kPa); 65 psf (3.11 kPa); or 68.9 psf (3.29 kPa)**>> in accordance with <<ASTM E330/E330M>>.
10. Wind Load: Not required.
11. Curtain Material:
- a. Galvanized Steel: << **18 gauge, 0.0516 inch (1.31 mm); 20 gauge, 0.0396 inch (1.01 mm); 22 gauge, 0.0336 inch (0.86 mm); or _____ gauge, _____ inch (_____ mm)**>>.
 - b. Aluminum: << **0.050 inch (1.27 mm); or _____ inch (_____ mm)**>>.
 - c. Stainless Steel: << **20 gauge, 0.0359 inch (0.91 mm); or _____ gauge, _____ inch (_____ mm)**>>.
 - d. Slat Profile: << **C-187; C-275; F-265; or FE-265**>>.
 - e. Fenestrated Slats: << **Not required; Perforated holes; 5/8 by 3 inches (16 by 76 mm); 1 by 10 inches (25 by 254 mm); 5/8 by 3 inches (16 by 76 mm) with Plexiglass covers; or 1 by 10 inches (25 by 254 mm) with Plexiglass covers**>>.
 - f. Galvanized Steel Finish:
 - 1) Standard polyester base coat.
 - (a) Color: << **Gray; Tan; White; or Brown**>>.
 - 2) << **PowderGuard Premium powder coat; PowderGuard Textured powder coat; or PowderGuard Max powder coat**>>.
 - (a) Color: << _____>>.
 - g. Aluminum Finish: << **Mill finish; Clear anodized; Black anodized; Bronze anodized; or PowderGuard Premium powder coat; _____ color**>>.
 - h. Stainless Steel Finish: << **No.2B mill; or No.4 satin**>>.
12. Bottom Bar: << **6063-T6 aluminum; Galvanized steel; or 304 Stainless steel**>>.
- a. Profile: << **Extruded T; Extruded tube; Double angle; or Single angle**>>.
 - b. Finish: << **Mill finish; Clear anodized; Black anodized; Bronze anodized; Hot-dip galvanized; PowderGuard Premium powder coat; PowderGuard Textured powder coat; PowderGuard Zinc powder coat; Stainless No.4 satin; or Stainless No.2B mill**>>.
 - 1) Color: << **Black; Match curtain; or _____**>>.
13. Locking Options to Include: << **None; Slide lock; Cylinder; or Best cylinder**>>.
- a. Lock Locations: << **Both jambs; Left only; or Right only**>>.
 - b. Lock Access: << **Coil side; or Opposite coil side**>>.
14. Weatherstripping and Seals:

- a. Bottom Seal Astragal: << **Required**; or Not required>>.
 - b. Interior Guide Seal: << **Required**; or Not required>>.
 - c. Exterior Guide Seal: << **Required**; or Not required>>.
 - d. Lintel Brush Seal: << **Required**; or Not required>>.
15. Side Guides, Channels: Constructed of << **steel**; 304 stainless steel; or **aluminum**>> with members fully bolted together.
- a. Finish: << **Mill finish**; Clear anodized; Black anodized; Bronze anodized; Hot-dip galvanized; PowderGuard Premium powder coat; PowderGuard Textured powder coat; PowderGuard Zinc powder coat; Stainless No.4 satin; or Stainless No.2B mill>>.
 - 1) Color: << **Black**; Match curtain; or _____>>.
16. Brackets: << **Steel**; or 304 Stainless steel>> to support counterbalance and curtain.
- a. Finish: << **Hot-dip galvanized**; Stainless No.4 satin; PowderGuard Premium powder coat; black color; PowderGuard Premium powder coat; _____ color; PowderGuard Textured powder coat; _____ color; or PowderGuard Zinc powder coat; _____ color>>.
17. Counterbalance: Helical torsion spring type, housed in steel tube or pipe barrel and supporting curtain with deflection limited to << **0.03 inch per foot (1:400 mm/sec)**>> of span. Adjustable spring tension required.
18. Hood: << **24 gauge, 0.028 inch stainless steel (0.63 mm stainless steel)**; Aluminum; **Not required**; or _____>>.
- a. Finish: << **Match curtain**; **Standard polyester base coat; gray color**; Standard polyester base coat; tan color; Standard polyester base coat; white color; Standard polyester base coat; brown color; Galvanized G90 (Z275); Gray-primed galvanized G90 (Z275); Clear anodized; Black anodized; Bronze anodized; Mill finish; PowderGuard Premium powder coat; _____ color; or PowderGuard Textured powder coat; _____ color>>.
19. Manual Operation: << **Push-up**; Chain hoist; or Crank>>.
20. Motor Operation: << **Not required**; or **Provide UL-listed electric operator; size as recommended by manufacturer to move door in either direction at minimum 8 inches (203 mm), maximum 1 foot (305 mm) per second**>>.
- a. Manual Override: << **Hoist**; Hoist and jackshaft release; or Jackshaft release>>.
 - b. Timer to Close: << **Not required**; or Automatic closing controlled by adjustable hold-open time delay>>.
 - c. Operation Supply Voltage: << **115/208/230V 1-phase 60Hz**; 208/230/460V 3 phase 60Hz; 575V 3-phase 60Hz; 220V 1-phase 50Hz; 220V 3-phase 50Hz; or 400V 3-phase 50Hz>>.
 - d. Signaling Device: << **Horn and strobe combination**; or Traffic warning light>>.
 - e. Actuation Device: Provide << **push button**; **key switch**; **pull cord**; **loop detector**; **motion detector**; **treadle switch**; and **radio control**>>.
 - f. Motor Mounting: << **Wall-mounted**; or Front of hood>>, << **right-hand side**; or left-hand side>>.
 - g. Motor Enclosure: << **Not required**; NEMA 4-12 watertight and oiltight; NEMA 4X corrosion-resistant; Totally enclosed, fan-cooled motor; or Totally enclosed, non-ventilated>>.

- h. Obstruction Safety Detection: Constant contact button only.
- i. Obstruction Safety Detection:
 - 1) Primary, Monitored:
 - (a) Photo Eyes: << **Reflective photo-eyes; Thru-beam photo-eyes; or NEMA 4X photo-eyes**>>.
 - (b) Light Curtain: << **3 feet (0.91 m); 6 feet (1.83 m); or _____ feet (_____ m)**>>.
 - (c) Safety Edge: << **2-wire reversing safety edge; Wireless reversing safety edge; or _____**>>.
 - 2) Secondary, Non-Monitored:
 - (a) Photo Eyes: << **Reflective photo-eyes; Thru-beam photo-eyes; or _____**>>.
 - (b) Light Curtain: << **3 feet (0.9 m); 6 feet (1.8 m); or _____ feet (_____ m)**>>.
 - (c) Safety Edge: << **2-wire reversing safety edge; or _____**>>.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify << **existing conditions; and _____**>> meet manufacturer's requirements before starting work.
- B. Verify opening sizes, tolerances and conditions are acceptable.

3.02 INSTALLATION

- A. Install in accordance with manufacturer's written instructions.
- B. Use anchorage devices to securely fasten assembly to wall construction and building structure without distortion or stress.
- C. Securely and rigidly brace components suspended from structure.<< **Secure guides to structural members only.; _____.; or None - N/A**>>
- D. Fit and align assembly including hardware; level and plumb, to provide smooth operation.
- E. Coordinate installation of electrical service; see Section 260583.
- F. Install enclosure and perimeter trim.

3.03 TOLERANCES

- A. Maintain dimensional tolerances and alignment with adjacent work.
- B. Maximum Variation from Plumb: << **1/16 inch (1.6 mm); or _____ inch (_____ mm)**>>.
- C. Maximum Variation from Level: << **1/16 inch (1.6 mm); or _____ inch (_____ mm)**>>.
- D. Longitudinal or Diagonal Warp: Plus or minus << **1/8 inch per 10 feet (3.2 mm per 3 m); or _____ inch per 10 feet (_____ mm per 3 m)**>>.

3.04 ADJUSTING

- A. Adjust operating assemblies for smooth and noiseless operation.

3.05 CLEANING

- A. See Section 017000 - Execution and Closeout Requirements for additional requirements.
- B. Clean installed components.

C. Remove labels and visible markings.

3.06 PROTECTION

A. Protect finishes until completion of project.

B. Touch up damaged finishes after Substantial Completion.

END OF SECTION