

The Genuine. The Original.



EDGE OF DOCK LEVELER

SPECIFICATIONS

DIMENSIONS/CAPACITY/APPLICATION

Model E66R	66"
Model E72R	72"
Weight Capacity	20,000, 30,000 lbs CIR
Ideal Application	Captive fleet, cost-effective reliability

BUMPER BOXES STANDARD

Molded Rubber Bumpers	√ Standard
Laminated Rubber Bumpers	Optional
Steel Faced Bumpers	Optional

LIP

15" Lip (Choose: Reg, Mid, High, Flat Crown)	√ Standard
17" Lip	Optional
Lip Bevel	√ Standard
Steplodge Overreach Lip	Optional

OPERATION

Operating Range 5" Above/Below Dock	√ Standard
Working Range 3" Above/Below Dock	√ Standard
Auto Return to Store	√ Standard
Self Storing Handle	√ Standard

SAFETY

Tethered Maintenance Brace	√ Standard
Safety Tread on Deck & Lip	√ Standard



1-Year Limited Warranty.

Warranty on dock equipment extends to **2-year limited when paired and purchased with the door.**

SAFE Features.

Engineered with integrated bumpers, ergonomic lift mechanisms, and accessible service points to support safer installation, operation, and upkeep.

- Returns to stored position in event truck pulls away



Patent-pending textured powder coat delivers unmatched slip resistance and preserves finish in high-traffic environments



Updated Tethered maintenance brace for better safety during planned maintenance and service

SMOOTH Transitions.

Heavy-duty construction and precision-machined lip deliver consistent, secure trailer engagement—protecting crews, cargo, and bottom lines.

- Meets ANSI MH30.1-2022 standards for strength and durability—proven to support a 10-year structural life
- Quick, Easy, removable handle provides effortless operation



Mounting Options - Approach Plates, Formed Angles, Wall Plates, Channel Embeds

SMART Designs.

Compact, bolt-on design with pre-mounted components simplifies install and minimizes maintenance—ideal for fast-paced dock environments.

- Environmental Compliance - U.S. EPA recommended eco-friendly coating process



Improved operation handle, reduced travel activation, removable with storage clip



Lip control

- Lower hole - more control
- Upper hold - extended lip landing
- Field adjustable

Mounting Options:



Approach Plates

Create a continuous trailer-to-building path that improves safety, efficiency, and protection during loading.




Wall Plates

For vertical mounting, ensures alignment and long-lasting support.



Formed Angles

Reinforce high-traffic, heavy-load areas to extend leveler performance.



Channel Embeds

Seamlessly integrate with concrete for a stable, durable foundation.

©2026 Overhead Door Corporation. Overhead Door is a trademark and the Red Ribbon logo is a registered trademark of Overhead Door Corporation. All other trademarks are the property of their rightful owners. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.

