


WindStorm™ MODEL 7565

WIND LOAD-RATED GARAGE DOORS



Model 7565, V Shaped Overlay panel, Terra Bronze finish, Stockbridge windows, decorative hardware


Featuring beautiful carriage house designs and durable construction to enhance your home's curb appeal and protect it from nature's fury. Stringently tested to meet wind load requirements.

- Available with impact rated options and reinforced hardware throughout the door
- Designed to meet local building codes – when ordered with specified wind load requirements – including Miami-Dade County
- Durable overlays are specially treated to resist termites, weather and fungal decay.
- Joint seals – snug-fitting tongue-and-groove section joints reduces wind and weather from entering the garage.
- Limited Lifetime warranty that protects against section rust-through for as long as you own your home. Also included is a one-year non-transferable, Limited warranty ensuring high standards for materials and workmanship.
- Specified foamed-in-place polyurethane insulation – with a U-factor¹  of 0.15 and an R-value² of 12.12 can improve the thermal efficiency of your garage space, reduce street noise and make the door operate more quietly.

- 1 - U-factor is independently tested and verified per ANSI/DASMA 105 using solid doors and specific product sizes.
- 2 - Overhead Door Corporation uses a calculated door section R-value for our insulated doors.



Overhead Door™ Brand participates in the DASMA Thermal Performance Verification Program. The program verifies the thermal performance of sectional garage doors. The lower the U-factor rating, the better the thermal performance.

 Symbol indicates verified U-factor rating in accordance with the DASMA Thermal Performance Verification Program.

The Genuine. The Original.




Select your door panel style


1 Choose a panel style

Panels below shown in square and arched top.


Horizontal Overlay (H1)




Horizontal Overlay (H3)




Vertical Overlay (C5)




Horizontal Overlay (H4)




Vertical Overlay (C4)




A Shaped Overlay (A)




X Shaped Overlay (X)




A Shaped Overlay (A2)




Horizontal Overlay (H)



Horizontal Overlay (H2)



V Shaped Overlay (V)



| MODEL | WOOD GRAIN TRIM | POLYURETHANE INSULATION | U-FACTOR* | R-VALUE** | OVERLAY THICKNESS | DOOR THICKNESS | COMMERCIAL TRACK | RESIDENTIAL TRACK | BALL BEARING ROLLERS/NYLON TIRES | WARRANTY |
|-------|-----------------|-------------------------|-----------|-----------|-------------------|----------------|------------------|-------------------|----------------------------------|------------------|
| 7565 | ● | ● | 0.15 | 12.12 | 3/8" | 1 3/8" | Optional | ● | ● | Limited Lifetime |

* U-factor is independently tested and verified per ANSI/DASMA 105 using solid doors and specific product sizes.

** Overhead Door Corporation uses a calculated door section R-value for our insulated doors.

Building code/agency requirements

| EXPOSURE B | DOOR WIDTH UP TO | WIND SPEEDS/DESIGN PRESSURES MPH1/MPH2/PSF DESIGN PRESSURE | IMPACT RESISTANT | GLASS AVAILABLE | |
|------------|------------------|--|------------------|-------------------------|-------------------------|
| | | | | STANDARD | IMPACT |
| Model 7565 | 9' | 95 - 125 mph ¹ / 120 - 265 mph ² (+12.80/-14.80) - (+64.00/-72.00) | Yes ³ | Long panel ³ | Long panel ³ |
| | 16' | 95 - 190 mph ¹ / 120 - 230 mph ² (+12.40/-13.80) - (+46.00/-52.00) | Yes ³ | Long panel ³ | Long panel ³ |
| | 18' | 100 - 190 mph ¹ / 120 - 230 mph ² (+12.40/-13.80) - (+46.00/-52.00) | Yes ³ | Long panel ³ | Long panel ³ |

¹ Wind Speed based on ASCE 7-22 has 3-Second Peak gusts, using Exposure C, for single or double story structures. Assumptions: Mean roof height of 25 ft, flat ground, at sea level, enclosed building and roof angle >10°. The Wind Speed Calculation is based on the max width of the door and a max height of 8-7 ft depending on the section heights. If a narrower, or taller door is used instead of the max shown in the chart, the wind speed rating may be different. The wind speeds are listed as a guide only. Wind speed is only one of many factors that determine the design pressure on a structure. The design and location for the structure can have a great effect on the loads placed on the garage door. Consult a registered architect or structural engineer to determine what design pressure is appropriate for your application.

² Wind Speed based on ASCE 7-22 has 3-Second Peak gusts, using Exposure B, for single or double story structures. Assumptions: Mean roof height of 25 ft, flat ground, at sea level, enclosed building and roof angle >10°. The Wind Speed Calculation is based on the max width of the door and a max height of 8-7 ft depending on the section heights. If a narrower, or taller door is used instead of the max shown in the chart, the wind speed rating may be different. The wind speeds are listed as a guide only. Wind speed is only one of many factors that determine the design pressure on a structure. The design and location for the structure can have a great effect on the loads placed on the garage door. Consult a registered architect or structural engineer to determine what design pressure is appropriate for your application.

³ Options available on select models.

- Wind load drawings available upon request.
- Wind speeds listed in this guide are provided for reference purposes only.
- In ALL cases the local building authority is the sole and final determiner of the structural and safety requirements, and suitability of the garage door.

Customize your door with texture, color, windows and decorative hardware

2 Choose a texture and color

Overlay texture options



Wood grain - standard



Smooth - optional

Color options



White/White




Almond/White




Sandstone/White



Terra Bronze



Brown/White



Black/White

Door overlays and window trim are available in the colors shown or can be painted to match your home's decor (additional charges may apply). Actual colors may vary from brochure due to fluctuations in the printing process. **Always request a color sample from your Overhead Door™ Distributor for accurate color matching before ordering your door.**

3 Choose a window style

Contact your Overhead Door™ Distributor to determine window availability and your local building official for code requirements.

Non-impact windows



Clear Long



Stockbridge



Stockton



Stockton Arch



Somerton



Wyndbridge

Impact windows



Clear Long Impact



Stockbridge Impact



Stockton Impact



Stockton Arch Impact




Somerton Impact



Wyndbridge Impact

4 Choose your decorative hardware

Spear pull handles and bottom lift handle are included with door.



Spear

Additional decorative hardware options shown below. See website for complete hardware selection.



Spear Hinge (16" and 18" available)

Bean Hinge (16" only)

Spade Design Hinge

Bean Design Handle

Large Hammered Iron Handle

5 Choose your opener



Be sure to ask about our complete line of Overhead Door® garage door openers. Powerful, quiet and durable, these garage door openers are designed for performance, safety and convenience. Your Overhead Door™ Distributor will help you choose the opener that best suits your door and preferences.

Transform Your Home with the DoorView® Visualization Tool.

Go to overheaddoor.com to try our online interactive software tool that lets you visualize what your home would look like with a new Overhead Door™ garage door. Contact your local Overhead Door™ Distributor for more information and to receive a quote.



BEFORE



AFTER

Model 7565, Vertical Overlay, Almond/White finish, Stockbridge windows, decorative hardware

The Genuine. The Original.

Since 1921, Overhead Door Corporation has not only raised the standards of excellence for the industry – we’ve created them. We created the first sectional garage door in 1921 and the first electric garage door opener in 1926.

Today, our network of over 400 Overhead Door™ Distributors are still leading the way with innovative solutions and unmatched installation, service and support. So look for the Red Ribbon. It’s your guarantee that you’re getting the genuine, the original Overhead Door™ products and services.

SOLD AND DISTRIBUTED BY:



The Genuine. The Original.



2501 S. State Hwy. 121 Bus., Suite 200, Lewisville, TX 75067
1-800-929-DOOR • sales@overheaddoor.com
www.overheaddoor.com